

R135 GEN:2

SKID LOADER

GEHL®



KEY FEATURES

- ✓ NEW Low Effort Control Choices
- ✓ All-Tach® Attachment System (Universal-Type)
- ✓ Self-Leveling Hydraulic Lift Action
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS Level II
- ✓ Dual T-Bar or Hand/Foot Control System
- ✓ Audible Back-Up Alarm
- ✓ Standard High Back Cushion Seat

KEY SPECIFICATIONS

- ✓ Operating capacity (50%) – 612 kg (1,350 lbs.)
- ✓ Overall height to top of ROPS – 1930 mm (76")
- ✓ Gross Power – 34.3 kW (46.6 hp) @ 2800 rpm
- ✓ Yanmar / 4TNV88-BKMSR2 / Stage 3A
- ✓ 146.2 Nm (108 ft.-lbs.) @ 1820 rpm max torque
- ✓ 2784 mm (110") height to hinge pin
- ✓ 1364 mm (53.7") machine width - less bucket
- ✓ 2327 kg (5,130 lbs.) operating weight

R135 GEN:2 SKID LOADER



SPECIFICATIONS

	IMPERIAL	METRIC	
DIMENSIONS	Overall Operating Height - Fully Raised	143.8"	3653 mm
	Height to Hinge Pin - Fully Raised	110"	2790 mm
	Overall Height to Top of ROPS	76"	1930 mm
	Overall Length with Bucket (w/o Counterweight)	120"	3048 mm
	Dump Angle at Full Height	40°	
	Dump Height - Fully Raised	83.6"	2120 mm
	Dump Reach at Full Height	23.3"	591 mm
	Maximum Rollback Angle at Ground	28°	
	Rollback Angle at Full Height	98°	
	Seat to Ground Height	33.3"	846 mm
	Wheelbase	37.4"	950 mm
	Overall Width - Less Bucket ^A	53.7"	1364 mm
	Bucket Width	54"	1372 mm
	Ground Clearance to Chassis	7.9"	201 mm
	Overall Length without Bucket (w/o Counterweight)	91.4"	2322 mm
	Rear Departure Angle	25°	
	Clearance Radius - Front with Bucket	72.5"	1842 mm
Clearance Radius - Front without Bucket	44.1"	1120 mm	
Clearance Radius - Rear (w/o Counterweight)	54"	1372 mm	
Standard Specification Tire Size	10.00x16.5 HD		
ENGINE	Make	Yanmar	
	Model	4TNV88-BKMSR2 Stage 3A	
	Gross Power @ 2800 rpm	46.6 hp	34.3 kW
	Net Power @ 2800 rpm	44.5 hp	33.2 kW
	Maximum Torque @ 1820 rpm	108 ft-lbs.	146.2 Nm
	Displacement	133.6 cu.in.	2.19 L
HYDRAULICS	Auxiliary Hydraulic Flow - Standard	18.5 gpm	70 L/min
	High-Flow Auxiliary Hydraulics - Opiton	N/A	
	Reservoir Capacity	9.2 gal.	34.8 L
ELECTRICAL	Battery	12-volt	800 CCA
	Starter	12-volt	2.3 kW
	Alternator	100-amp	
CAPACITIES / WEIGHTS	Rated Operating Capacity ^B	1,350 lbs.	612 kg
	Rated Operating Capacity with Optional Counterweight ^B	1,500 lbs.	680 kg
	Fuel Tank	15.7 gal.	59.4 L
	Travel Speed - Maximum	8.0 mph	12.9 km/hr
	Travel Speed with Two-Speed Option - Maximum	N/A	
	Operating Weight ^C - Approximate	5,130 lbs.	2327 kg
SOUND / VIBRATION*	Noise Level / Environmental Level	101 dB	
	Operator Ear	85 dB	
	Hand / Arm Vibration	1.77 m/s ²	
	Whole Body Vibration	.81 m/s ²	

* Standard seat option and T-Bar controls

A Overall width is dependent upon the amount of wheel offset

B Per SAE J8181, SAE J732, and ISO 14397

C Weight of base unit with standard equipment, standard tires (heavy-duty flotation), standard dirt-construction bucket and 175 lbs. (79 kg) operator.

GEHL reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

GEHL reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

STANDARD FEATURES

- NEW Choice of NEW LOW EFFORT Servo-Assist T-Bar or Servo Assist Hand/Foot Controls
- Fuel Gauge with Real Time Fuel Consumption
- All-Tach™ Attachment System (Universal-Style)
- Warning Lamps and Buzzer – Engine and Hydraulic Oil Temperature
- Battery Charge Indicator Lamp
- Low Oil Pressure Light and Buzzer
- Seatbelt Indicator Lamp and Buzzer
- Coolant Temperature Gauge
- Hourmeter
- Manual-Control Hydrostatic Drive
- ROPS/FOPS- Level II – Approved Overhead Guard
- Operator Restraint Bar with Armrests
- Independent Hydraulic Reservoir and Hydraulic Oil Cooler
- Audible Back-Up Alarm
- Engine Intake Air Pre-Heater Starting Assist
- Adjustable Seatbelt
- Lift Arm Support Device
- Hydraloc™ System
- Dual Front and Rear Work Lights
- Dual, Integral Cleanout Plates
- Vandalism Lock Provisions - Fuel and Engine Cover
- Top and Rear Windows
- Acoustical Sound Material and Deluxe Headliner
- Deluxe High Back, Cushion Seat
- Front Auxiliary Hydraulics with 3/4-inch Flat-Faced Couplers
- Visual Hydraulic Filter Indicator
- Power Plug (12 V)
- Horn

OPTIONAL FEATURES

- NEW LOW EFFORT Optional Pilot Joystick Controls with Hydraglide Ride Control System
- Power-A-Tach® - Hydraulic Powered Attach System
- Engine Block Heater
- Suspension Seat
- Cab Door with Wiper
- Sliding Side Windows
- Heater/Defroster
- Bluetooth Radio & Speakers
- 3-inch Wide Seatbelt – When Required by Law
- Rear View Mirror
- Engine Auto-Shutdown System
- Interior Dome Light
- Centrifugal Pre-Cleaner
- Strobe Light
- Impact-Resistant Door
- Lift Kit - Single Point Lift System
- Rear Counterweight (increases Rated - Operating Capacity by 150 lbs. (68 kg) and adds 1.5" (38 mm) to length
- Bucket Bolt-On Cutting Edge
- Self-Leveling Lift Action
- Easy Manager Telematics
- Battery Disconnect Switch
- Work Light Kit (LED)



geh.com

One Gehl Way, West Bend, WI 53095

Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT