

Overall Operating Height - Fully Raised 4013 mm 158 in Height to Hinge Pin - Fully Raised 3061 mm 121 in Overall Height to top of ROPS 2032 mm 80 in Dump angle at full height 42 ° 42° 2286 mm Dump height 90 in Overall length with bucket 3543 mm 139 in Dump reach - Full height 851 mm 34 in Rollback Angle at Full Height 92° 92° Seat to ground height 952.50 mm 37 in Overall width less bucket 1623 mm 64 in Ground clearance 178 mm 7 in Overall length - Less Bucket 2743 mm 108 in Clearance Radius - Front with Bucket 2146 mm 84 in 66 in Clearance Circle - Rear 1664 mm Travel Speed with Two-Speed Option - Maximum 18.70 km/h 12 mph Travel speed (unladen) 12.10 km/h 8 mph Engine Engine brand Yanmar Yanmar Engine model 4TNV98C-NGL 4TNV98C-NGL Engine norm Stage V Stage V Gross Power (kW) 52.70 kW 70.7 hp Net Power (kW) 51.70 kW 69.3 hp Max. torque / Engine rotation 241 Nm / 1625 rpm 178 ft/lbs / 1625 rpm Number of cylinders Engine cooling system Water Battery voltage 12 V 12 V 100 A Alternator - Ampere 100 A Starter (kW) 3 kW 4 hp 86.50 l/min Standard flow - Auxiliary hydraulics 23 US gpm

Auxiliary Hydraulic Pressure

Reservoir Capacity Hydraulics

Tank capacities Fuel tank

High-Flow Auxiliary Hydraulics - Option

High-Flow Auxiliary Hydraulics Pressure - Option

239.59 bar

114 l/min

229.25 bar

22 70 1

3.30 l

3475 PS

30 US gpm

3325 PSI

28 US gal

6 US gal

0.87 US gal





weather? Look no further than the mid-sized V210, a vertical lift Skid Loader completely redesigned to keep moving through thick and thin. Balancing power and maneuverability in a single machine, this durable and capable Skid Loader boasts 2,100lbs. of rated operating capacity—add an optional counterweight to lift even more. Its small frame and highly

Does your daily grind involve uneven terrain, demanding conditions, and unpredictable

and focused on the task at hand. This sturdy, multi-purpose machine tackles daily tasks with ease and ensures you're ready to adapt to whatever challenges come your way.

durable tires make space-constrained worksites a breeze to navigate, keeping you working



CONTROL TYPES

952 kg **OPERATING CAPACITY** [AT 50% TIPPING LOAD]

3.06 m **HEIGHT TO HINGE PIN** [FULLY RAISED]