



R135 GEN:2

Capacities	Metric	Imperial
Rated Operating Capacity	612 kg	1350 lb
Rated Operating Capacity with Optional Counterweight	680 kg	1499 lb
Unladen weight	2383.62 kg	5255 lb
Weight and dimensions		
Overall Operating Height – Fully Raised	3670.30 mm	144 in
Height to Hinge Pin – Fully Raised	2790 mm	110 in
Overall Height to Top of ROPS	1930 mm	76 in
Dump angle at full height	40 °	40 °
Dump height	2120 mm	83 in
Overall length with bucket	3073.40 mm	121 in
Dump reach – Full height	591 mm	23 in
Rollback at ground	28 °	28 °
Seat to ground height	871.22 mm	34 in
Wheelbase	950 mm	37 in
Overall width less bucket	1364 mm	54 in
Bucket Width	1372 mm	54 in
Ground clearance	201 mm	8 in
Overall length – Less Bucket	2359.66 mm	93 in
Clearance Radius – Front with Bucket	1842 mm	73 in
Clearance Circle – Front without Bucket	1120 mm	44 in
Clearance Circle – Rear	1372 mm	54 in
Performances		
Travel speed (unladen)	12.90 km/h	8 mph
Wheels		
Standard tires	10.00x16.5 HD	10.00x16.5 HD
Engine		
Engine brand	Yanmar	Yanmar
Engine model	4TNV88C	4TNV88C
Engine norm	Stage IV / Tier 4 Final	Stage IV / Tier 4 Final
Gross Power (kW)	34.30 kW	46 hp
Net Power (kW)	33.20 kW	44.5 hp
Max. torque / Engine rotation	146.20 Nm / 1820 rpm	108 ft/lbs / 1820 rpm
Battery	12 V	12 V
Starter (kW)	2.30 kW	3.08 hp
Hydraulics		
Standard flow – Auxiliary hydraulics	63.60 l/min	17 US gpm
Tank capacities		
Fuel tank	59.40 l	16 US gal
Displacement	2.19 l	0.58 US gal
Noise and vibration		
Environmental noise (LWA)	101 dB	101 dB
Whole-Body Vibration (ISO 2631-M)	0.81 m/s ²	0.81 m/s ²
Vibration to whole hand/arm	< 1.77 m/s ²	< 1.77 m/s ²



Born through the challenges of farm work but built for success everywhere else, the compact R135 GEN:2 delivers extra lifting capacity for those who need a nimble yet strong Skid Loader. Featuring power where it matters, this machine easily navigates through narrow gates and is more manageable during transport—getting you to wherever work needs doing, without causing a commotion. This new version of the R135 is packed with intuitive controls and designed for comfort, helping reduce operator fatigue during long days on the job. Low-effort controls make difficult jobs a cinch, and an air-ride seat along with other optional features means you'll go home at the end of a tough day without feeling like you've been hit by a ton of bricks.

CONTROL TYPES

OPTIONAL



T-BAR



HAND/FOOT



JOYSTICK

612 kg
OPERATING CAPACITY
[AT 50% TIPPING LOAD]

2.79 m
HEIGHT TO HINGE PIN
[FULLY RAISED]