

**VERTICAL
LIFT**



V330 GEN:2

CONTROL TYPES

OPTIONAL



DUAL-HAND



JOYSTICK

Job-tested for the most demanding environments, the V330 Skid Loader is a true workhorse. With enhanced visibility to help operators spot potential hazards and an intuitive, ergonomic cabin that enables precision maneuvering, this machine can help your operations overcome day-to-day challenges. And if loading trucks is part of your daily grind, the V330 gives you impressive reach at full height for material handling. From construction site to the farm to the lumber yard, it's time to make your own path with a machine that's strong, durable, and capable — a machine that works like you.

1497 kg
OPERATING CAPACITY
[AT 50% TIPPING LOAD]

3.3 m
HEIGHT TO HINGE PIN
[FULLY RAISED]

1.9 m
BUCKET WIDTH
[STANDARD]



Capacities	Metric	Imperial
Rated Operating Capacity	1497 kg	3300 lb
Unladen weight	4123 kg	9090 lb
Weight and dimensions		
Overall Operating Height - Fully Raised	4369 mm	172 in
Height to Hinge Pin - Fully Raised	3332 mm	131 in
Overall Height to Top of ROPS	2083 mm	82 in
Dump angle at full height	42 °	42 °
Dump height	2502 mm	99 in
Overall length with bucket	3874 mm	153 in
Dump reach - Full height	813 mm	32 in
Rollback at ground	29 °	29 °
Seat to ground height	1041 mm	41 in
Wheelbase	1257 mm	49 in
Overall width less bucket	1819 mm	72 in
Bucket Width	1880 mm	74 in
Ground clearance	229 mm	9 in
Overall length - Less Bucket	3023 mm	119 in
Clearance Radius - Front with Bucket	2400 mm	94 in
Clearance Circle - Front without Bucket	1422 mm	56 in
Clearance Circle - Rear	1765 mm	69 in
Performances		
Travel Speed with Two-Speed Option - Maximum	20.10 km/h	12 mph
Travel speed (unladen)	13.50 km/h	8 mph
Wheels		
Standard tires	14.00x17.5 HD	14.00x17.5 HD
Engine		
Engine brand	Yanmar	Yanmar
Engine model	4TNV98CT Stage V	4TNV98CT Stage V
Engine norm	Stage V	Stage V
Gross Power (kW)	53.70 kW	72 hp
Net Power (kW)	52.70 kW	70.7 hp
Max. torque / Engine rotation	294.20 Nm / 1625 rpm	217 ft/lbs / 1625 rpm
Battery	12 V	12 V
Starter (kW)	3 kW	4 hp
Hydraulics		
Standard flow - Auxiliary hydraulics	89 l/min	24 US gpm
High-Flow Auxiliary Hydraulics - Option	132 l/min	35 US gpm
Tank capacities		
Fuel tank	92.70 l	24 US gal
Reservoir Capacity Hydraulics	40 l	11 US gal
Displacement	3.30 l	0.87 US gal
Noise and vibration		
Environmental noise (LWA)	101 dB	101 dB
Whole-Body Vibration (ISO 2631-1)	1.07 m/s ²	1.07 m/s ²
Vibration to whole hand/arm	< 1.50 m/s ²	< 1.50 m/s ²