



1640

Capacities	Metric	Imperial
Rated Operating Capacity	386 kg	851 lb
Unladen weight	1352 kg	2981 lb
Weight and dimensions		
Overall Operating Height - Fully Raised	3167 mm	125 in
Height to Hinge Pin - Fully Raised	2438 mm	96 in
Overall Height to Top of ROPS	1897 mm	75 in
Dump angle at full height	46 °	46 °
Dump height	1836 mm	72 in
Overall length with bucket	2576 mm	101 in
Dump reach - Full height	376 mm	15 in
Rollback at ground	30 °	30 °
Seat to ground height	879 mm	35 in
Wheelbase	775 mm	31 in
Overall width less bucket	909 mm	36 in
Bucket Width	914 mm	36 in
Ground clearance	150 mm	6 in
Overall length - Less Bucket	1905 mm	75 in
Clearance Radius - Front with Bucket	1473 mm	58 in
Clearance Circle - Front without Bucket	833 mm	33 in
Clearance Circle - Rear	1097 mm	43 in
Performances		
Travel speed (unladen)	8.90 km/h	6 mph
Wheels		
Standard tires	8.70 x 12	8.70 x 12
Engine		
Engine brand	Yanmar	Yanmar
Engine model	3TNV82A-BPMSR Stage V Compliant	3TNV82A-BPMSR Stage V Compliant
Engine norm	Stage V	Stage V
Gross Power (kW)	18.10 kW	24.3 hp
Net Power (kW)	17.90 kW	24 hp
Max. torque / Engine rotation	86 Nm / 2400 rpm	63 ft/lbs / 2400 rpm
Battery	12 V	12 V
Starter (kW)	1.70 kW	2.3 hp
Hydraulics		
Standard flow - Auxiliary hydraulics	38.20 l/min	10 US gpm
Tank capacities		
Fuel tank	29 l	8 US gal.
Reservoir Capacity Hydraulics	27.30 l	7 US gal.
Displacement	1.30 l	0.34 US gal.



BUCKET WIDTH 914mm

1.9m

1.9m LENGTH WITHOUT BUCKET

2.58m

This ultra-compact skid loader carries its weight on the jobsite. The smallest skid loader manufactured by GEHL. It's easy to transport and tow and it will quickly get you a return on your investment. Also, great to grow your rental fleet and equip the DIY weekend warrior. Small in size but built tough and job-tested for years by GEHL customers. You can trust the 1640E to be your reliable co-worker rain or shine.

CONTROL TYPES

OPTIONAL



T-BAR

386 kg
OPERATING CAPACITY
[AT 50% TIPPING LOAD]

2.4 m
HEIGHT TO HINGE PIN
[FULLY RAISED]