

# V360

## COMPACT LOADERS

**GEHL**®



### KEY FEATURES

- ✓ NEW Color Display with Keyless Start + Security Code
- ✓ NOW STANDARD Pilot Joystick Controls
- ✓ NEW Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Variable Hydraulics with Drain Case
- ✓ NEW LED Work, LED Rear Lights + Egress Lighting

|                                      |  | METRIC            |
|--------------------------------------|--|-------------------|
| CAPACITIES                           | Operating Capacity At 50% Tipping Load               | 1633 kg           |
|                                      | Rated Operating Capacity with Optional Counterweight | 1723.65 kg        |
|                                      | Operating Weight                                     | 4681 kg           |
|                                      | Tipping capacity                                     | 3266 kg           |
| WEIGHT AND DIMENSIONS                | Wheelbase  | 1321 mm           |
|                                      | Overall Operating Height - Fully Raised              | 4435 mm           |
|                                      | Height to Hinge Pin - Fully Raised                   | 3454 mm           |
|                                      | Overall Height to top of ROPS                        | 2134 mm           |
|                                      | Dump angle at full height                            | 41 °              |
|                                      | Dump height  | 2678 mm           |
|                                      | Overall length with bucket                           | 3968 mm           |
|                                      | Dump reach - Full height                             | 798 mm            |
|                                      | Rollback Angle at Full Height                        | 94 °              |
|                                      | Seat to ground height                                | 1085 mm           |
|                                      | Overall width less bucket                            | 1916 mm           |
|                                      | Bucket Width   | 2134 mm           |
|                                      | Ground clearance                                     | 254 mm            |
|                                      | Overall length - Less Bucket                         | 3173 mm           |
| Clearance Radius - Front with Bucket | 2350 mm  |                   |
| PERFORMANCES                         | Travel speed (unladen)                               | 11.70 km/h        |
|                                      | Travel Speed with Two-Speed Option - Maximum         | 20 km/h           |
| WHEELS                               | Standard tires                                       | 14.00 x 17.5 HD   |
| ENGINE                               | Engine brand   | Deutz             |
|                                      | Engine model   | TCD3.6            |
|                                      | Max. torque / Engine rotation                        | 460 Nm / 1600 rpm |
|                                      | Power source   | Battery           |
|                                      | Engine power (Hp / kW)                               | 114 Hp / 85 kW    |
|                                      | Starter  | 4 kW              |
| HYDRAULICS                           | Standard flow - Auxiliary hydraulics                 | 94.60 l/min       |
|                                      | Auxiliary Hydraulic Pressure                         | 237.86 bar        |
|                                      | High-Flow Auxiliary Hydraulics - Option              | 151.40 l/min      |
|                                      | High-Flow Auxiliary Hydraulics Pressure - Option     | 237.86 bar        |
| TANK CAPACITIES                      | Fuel   | 106 l             |
|                                      | Hydraulic tank capacity                              | 27 l              |

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



## STANDARD FEATURES

- 12Volt Power Port
- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Back-Up Alarm
- Battery Disconnect
- Brake Control (Auto/Manual)
- Cup Holder
- Engine Auto-Shutdown System
- Engine Block Heater
- Foot Throttle
- High-Back Adjustable Seat
- Horn
- Hydraglide™ Ride Control
- Hydraloc™ Safety System
- Hydrostatic Drive - Servo
- Lift Arm Support Device
- Operator Restraint Bar
- Pilot Joystick Controls
- Profiled lift arms

## OPTIONAL FEATURES

- Adaptive air suspension heated fabric seat - With electric lumbar adjustment - GRAMMER
- Cabin with Heat and Air Conditioning
- Counterweight
- Electronic Attachment Control - 14-Pin Connector
- Engine Block Heater
- High-Flow Auxiliary Hydraulics
- IdealAccess™ Fold-Up Door
- LED front road lights
- Power-A-Tach® Attachment Mounting System
- Rearview Camera



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT