



Zoom snow plow

This new type snow plow is equipped with a straight main blade and two wings which can be extended and retracted steplessly, powered by two hydraulic cylinders. This gives several different working widths and makes the snow plow very versatile. The plow is also equipped with hinged end plates which can be turned down on the ground. This allows fast and efficient snow collecting. When the end plates are turned up over the blade the plow works as conventional dozer blade and moves snow quickly to the side – and is narrower as well. The end plates are spring loaded which means they follow the contours of the ground well.

Zoom snow plow requires the optional Opticontrol® on the loader. Extension and retraction of the wings and turning of the blade are operated with the switches of the switch pack. The wings can be extended one at a time or both at the same time. Working width is steplessly adjustable between 1,35 – 2,35 m. The telescoping tubes of the side wings are equipped with maintenance free wear pads. There is also a safety bolt for blade release at the top link, however as the blade is vertical it doesn't get stuck easily but rather jumps over obstacles.

The mounting frame of the zoom snow plow is the same as on the 2000 and 2500 mm dozer blades. It allows a ±10° vertical floating which can be locked if necessary. The plow is also equipped with ±30° hydraulic blade turning. Ice cutting edge is standard equipment.

Option:

- Ice scraper edges, kit A437890
- Straight cutting edge A437891
- Rubber edge A431475

- ✔ **Hydraulically extendable dozer blade allows snow removal also in smaller yards, on parking lots etc.**
- ✔ **Equipped with two wings which can be extended and retracted independently or both at the same time**
- ✔ **Steplessly adjustable working width between 1,35 – 2,35 m**
- ✔ **Hinged, foldable end plates for efficient snow collecting and moving**
- ✔ **Hydraulic blade turning ± 30° and vertical floating ± 10°**

| | |
|-------------------------|--------------|
| Working width | 1350-2350 mm |
| Max width | 1460-2460 mm |
| Max length | 993 mm |
| Blade turning angle | ± 30° |
| Vertical floating angle | ± 10° |
| Weight | 535 kg |
| Product no | A425180 |

The optional Opticontrol® is required on the loader.

| | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|-----|------|------|------|----|----|
| 220 | 225 | 423 | 523 | 528 | 530 | 630 | 635 | 640 | 645i | 650i | 735 | 755i | 760i | 860i | e5 | e6 |
| ✗ | ✗ | ✗ | ✗ | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ | ✔ | + | + |

Compatibility tables are advisory. Please contact your local Avant UK DEALER to make sure that the attachment is compatible with your Avant loader.